

COMPACTORS

Product Features

- Designed for optimum performance and durability.
- Premium quality hydraulic motor.
- The angle between rubber damper and vibrating plate maximizes pressure to the soil and minimizes stress to the machine.
- Highly effective in narrow ditch compacting.
- Optimal for road construction, building foundation and slope compaction.





Model	Unit	RC30	RC40	RC50	RC80	RC130
Impulse Force	lb	1,400	4,200	14,400	18,500	27,000
Cycles Per Minute	n/ min	2,200	2,200	2,200	2,200	2,000
Oil Flow	gpm	7-10	13-19	26-37	34-50	42-62
Base Plate Dimensions	in. (mm)	15.7×27.5 (400×700)	19.6×35.4 (500×900)	23.6×43.3 (600×1,100)	31.4×47.2 (800×1,200)	35.4×51.1 (900×1,300)
Operating Weight	lb	231	617	782	1,400	2,094
Operating Pressure	psi	2,030-3,045	2,030-3,045	2,030-3,045	2,030-3,045	2,030-2,610
Applicable Carrier	lb (ton)	5,500-8,800 (2.5-4)	8,800-19,800 (4-9)	22,000-39,600 (10-18)	39,600-50,700 (18-23)	50,700-70,500 (23-32)

 $[\]hbox{*Specification and features are subject to change without prior notice for improvement in quality.}$



Address: 1191 N. Patt St., Anaheim, CA 92801 Phone: (714) 879-5919 Fax: (714) 879-9149

E-mail: sales@rockwaterce.com www.rockwaterce.com

For sales and service, contact your Rockwater/ CB Dealer: